ECOLIFT

LOW-LEVEL ACCESS





STANDARD SPECIFICATIONS

Performance

Maximum working height4.20 mMaximum platform height2.20 mClosed platform height0.68 mWorking outreach0.65 m

Platform dimensions L x W 0.85 m x 0.64 m Working foot print 1.28 m x 0.74 m

Safe Working Load – Platform + Tray 150 kg (1 person + tools)

Maximum manual force 200 N Maximum gradient for operation 0,5°

Maximum wind forceInternal use only 0 m/sMaximum castor point load155 kg / 1.52 kNMaximum wheel force155 kg / 1.52 kNPower Sound Levelless than 70 dBA

Closed dimensions

 Length
 1.28 m

 Width
 0.74 m

 Height
 1.95 m

 Weight
 319 kg

Typical applications and uses

Use Indoor Use

Applications 1st & 2nd Fix. Pipe Work, M & E. FM.

Cleaning. Painting. Retail. Point of Sale. FM.

KEY SPECIFICATIONS

Platform carrying capacity:

150 kg

Dimension: 1.28 m x 0.74 m

Working Height:

4.20 m

Total Weight:

319 kg

KEY FEATURES

- Intuitive to operate turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble-free service
- Minimal operational costs, virtually maintenance free

STANDARD FEATURES

- Intuitive to operate turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (1.28 m x 0.74 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operating costs, virtually maintenance free
- Auto-lok brake on elevation
- Elevates only when operated
- Interlocked lifting mechanism
- Spirit Level
- Lanyard attachment
- Emergency lowering handle

- Forklift pockets
- Fold up step
- Rubber bump pads
- Durable powder coated finish
- Anti-climb basket with removable gates for emergency

ACCESSORIES & OPTIONS

ATEX

Tool Tethering options

Steel tool tray

vca

010 - 322 00 28

RENTAL @ SALES @ SERVICES @ ECRANES.eu



