

# ECOLIFT WR

LOW-LEVEL ACCESS



## STANDARD SPECIFICATIONS

### Performance

Maximum working height	4.20 m
Maximum platform height	2.20 m
Closed platform height	0.68 m
Working outreach	0.65 m
Platform dimensions L x W	0.85 m x 0.64 m
Working foot print	1.28 m x 0.95 m
Safe Working Load	150 kg (1 person + tools)
Maximum manual force	200 N
Maximum gradient for operation	3°
Maximum wind force	Internal/external use 12.5 m/s
Maximum castor point load	165 kg / 1.62 kN
Maximum wheel force	165 kg / 1.62 kN
Power Sound Level	less than 70 dBA

### Closed dimensions

Length	1.28 m
Width	0.95 m
Height	1.95 m
Weight	358 kg

## KEY SPECIFICATIONS

**Platform carrying capacity:** 150 kg  
**Dimension:** 1.28 m x 0.95 m

**Working Height:** 4.20 m  
**Total Weight:** 358 kg

## KEY FEATURES

- Intuitive to operate - turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Unlimited lift cycles, can be used 24/7
- Possibility to work indoor and outdoor
- Minimal operational costs, virtually maintenance free

## STANDARD FEATURES

- Wind rated for outdoor use (12.5 m/s)
- Intuitive to operate - turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (1.28 m x 0.95 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operating costs, virtually maintenance free
- Auto-lok brake on elevation
- Elevates only when operated
- Interlocked lifting mechanism
- Spirit Level
- Lanyard attachment
- Emergency lowering handle
- Forklift pockets
- Fold up step
- Rubber bump pads
- Lifting points
- Durable powder coated finish
- Anti-climb basket with removable gates for emergency

## ACCESSORIES & OPTIONS

- ATEX
- Tool Tethering options
- Steel tool tray

# 010 - 322 00 28

RENTAL SALES SERVICES ECRANES.eu

Weg en Land 10a · 2661 DB Bergschenhoek · info@ecranes.eu  
KvK 87664461 · BTW NL864363795.B01 · IBAN NL75ABNA0114815879

vca<sup>v</sup>

